



tesa[®] 4388 Easy Cover[®] Industry



Product Information

3-in-1 Masking solution for large areas industrial paint applications

Product Description

tesa[®] 4388 Easy Cover[®] Industry is a 3-in-1 system for masking large areas for industrial applications. The convenient system is comprised of the slightly crepe paper masking tape tesa[®] 4309 with natural rubber adhesive, a masking paper border and HDPE masking film, working together to ensure optimal protection. tesa[®] 4309 is a conformable and flexible paper masking tape. It is suitable for spray-painting applications, with subsequent oven-drying up to a temperature of 120°C. The additional masking paper border provides paint absorption at the most critical area close to the painting area. The HDPE film serves for the protection against spray particles. It is specifically treated for better paint adherence and clings to the to be painted object. tesa[®] 4388 Easy Cover[®] Industry allows a single person to cover large areas easily and quickly as well as reducing the logistic complexity.

Benefits:

- Ideal for masking large areas easily and quickly
- Temperature resistance up to 120°C
- Additional masking paper border providing excellent paint absorption
- Reduction of logistic complexity

Product Features

- Ideal for masking large areas easily and quickly
- Temperature resistance up to 120°C
- Reduction of logistic complexity
- Additional masking paper border providing excellent paint absorption
- tesa[®] 4388 Easy Cover[®] Industry allows a single person to cover large areas easily and quickly as well as reducing the logistic complexity.
- The additional masking paper border provides paint absorption at the most critical area close to the painting area.
- It is specifically treated for better paint adherence and clings to the to be painted object
- The HDPE film serves for the protection against spray particles.

Application Fields

- tesa[®] 4388 Easy Cover[®] Industry is recommended for professional masking during spray painting work for industrial applications
- The 3-in-1 system is ideal for masking large areas easily and quickly for the protection against spray particles
- tesa[®] 4388 Easy Cover[®] Industry can withstand temperatures of up to 120°C

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

For latest information on this product please visit <http://l.tesa.com/?ip=04388>



tesa[®] 4388 Easy Cover[®] Industry

Product Information

Product Construction

- | | | | |
|--------------------|-----------------------|-------------------|--------|
| • Backing | slightly-creped paper | • Total thickness | 170 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-------------------------------------|---------------------|
| • Elongation at break | 12 % | • Material of masking coverage | HDPE |
| • Tensile strength | 47 N/cm | • Thickness of masking coverage | 10 µm |
| • Easy to remove | yes | • Weight of addtl. protection paper | 37 g/m ² |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 3.5 N/cm |
|---------|----------|

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04388>