

tesa® 4319

Product Information



Strongly crêped paper masking tape for paint work and packaging purposes

Product Description

tesa® 4319 is a highly crêped, general purpose paper masking tape for various application fields.

Sustainable Aspects



For more information: https://www.tesa.com/product-sustainability

Application Fields

It is particularly suited for masking during paintwork, for under sealing and bundling as well as for edge protection of paper reels. The product offers a good tack.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	highly-creped paper •	•	Bio-based content of liner by	67 %
•	Type of adhesive	natural rubber		weight (acc. EN 16785)	
		•	,	Total thickness	375 μm

Properties/Performance Values

•	Elongation at break	58 %	•	Temperature resistance (30 min)	60 °C
•	Tensile strength	24 N/cm	•	Temperature resistance (60 min)	60 °C
•	Hand tearability	very good			

Adhesion to Values

Additional Information

Recommendation:

Stretching the crêped backing guarantees evenly defined paint edges and a good adhesion.



tesa® 4319

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

