tesa® 58399

Product Information

tesa® 58399 800 µm thermal conductive tape

Product Description

tesa® 58399 800 µm thermal conductive tape

Product Features

- This product is equipped with special acrylic adhesive that provide certain thermal conductivity when it applies between heat source and heat sink.
- It has good performance on polar substrates.

Application Fields

Applied between heat source and heat sink to transfer the heat.

- Battery module cooling plate mounting
- Power electronics unit
- FPC and PCB

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	none	• Color	white
• Type of adhesive	acrylic	• Color of liner	white
• Type of liner	PE-coated paper	• Thickness of liner	127 µm
• Total thickness	800 µm		

Product Assortment

• Available thicknesses	800 µm	• Available formats	Log roll, A4 sheet
• Available colors	white	• Available liners	paper

Properties/Performance Values

• Breakdown voltage	11 KV	• Temperature resistance (-40°C)	very good
• Density	1.5 g/cm^3	• Temperature resistance (125°C)	very good
• Flame retardancy	V2	• Temperature resistance short term	150 °C
• Hardness - Shore 00	75 STK		
• Release of liner	easy	• Thermal conductivity z-direction	1.3 W/mK

For latest information on this product please visit http://l.tesa.com/?ip=58399

tesa® 58399

Product Information

Adhesion to Values

- Steel (initial) 4.5 N/cm
- Steel (20min @ RT, 90°) 4.5 N/cm

Additional Information

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit http://l.tesa.com/?ip=58399