




# tesa<sup>®</sup> 52050

## Product Information



Blue single-sided PET self-adhesive tape

### Product Description

tesa<sup>®</sup> 52050 is blue single-sided self-adhesive tape consisting of a PET backing and a modified acrylic adhesive.

Special features:

- \* Thickness: 50µm
- \* Reliable bonding strength
- \* Excellent anti-repulsion property
- \* Good insulation property
- \* Good puncture resistance

### Product Features

- Thickness: 50µm
- Reliable bonding strength
- Excellent anti-repulsion property
- Good insulation property
- Good puncture resistance

### Application Fields

- FPC covering
- \* Components protection

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |          |                      |             |
|--------------------|----------|----------------------|-------------|
| • Backing          | PET film | • Total thickness    | 50 µm       |
| • Type of adhesive | acrylic  | • Color of liner     | transparent |
| • Type of liner    | PET      | • Thickness of liner | 50 µm       |

For latest information on this product please visit <http://l.tesa.com/?ip=52050>



# tesa<sup>®</sup> 52050

## Product Information

### Properties/Performance Values

- |                       |         |                                     |        |
|-----------------------|---------|-------------------------------------|--------|
| • Elongation at break | 30 %    | • Temperature resistance long term  | 80 °C  |
| • Tensile strength    | 22 N/cm | • Temperature resistance short term | 140 °C |

### Adhesion to Values

- |                      |          |                         |          |
|----------------------|----------|-------------------------|----------|
| • PC (initial)       | 4 N/cm   | • Steel (initial)       | 4.2 N/cm |
| • PC (after 14 days) | 5.2 N/cm | • Steel (after 14 days) | 5.4 N/cm |

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=52050>