

# tesa<sup>®</sup> Professional 53949 PV2 matt gaffer tape

**Product Information** 

Non-reflective polyethylene coated high grade cloth tape

### **Product Description**

tesa<sup>®</sup> 53949 PV2 is a matt gaffer tape specially designed for the arts and entertainment industry. It consists of a PE coated 80 mesh woven PET fabric backing coated with a pressure sensitive natural rubber adhesive. tesa<sup>®</sup> 53949 PV2 is the ideal solution for a wide range of applications whenever a non-reflective surface is important.

#### Features:

- light-absorbing, non-reflective
- good adhesion, even on rough surfaces
- abrasion resistant
- water repellent
- conformable
- easy to remove
- available in matt black, matt white, and matt silver

#### **Application Fields**

- On-stage/back-stage jobs in theatre, opera, cinema and music halls
- Fixing of cables on carpets, walls etc.
- Covering of shiny and glossy surfaces
- Fixing of cable links
- Sealing of joints
- Floor marking and fixing

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

<ul><li>Backing</li><li>Type of adhesive</li></ul>	PE extruded cloth natural rubber	•	Total thickness	310 µm
Properties/Performance Values				
<ul> <li>Elongation at break</li> <li>Tensile strength</li> <li>Abrasion resistance</li> <li>Ageing resistance (UV)</li> </ul>	85 N/cm		Hand tearability Humidity resistance Water resistance	good good good

#### **Additional Information**

Recommendation: please conduct a test on the application surface before using the product.

For latest information on this product please visit http://l.tesa.com/?ip=53949



# tesa<sup>®</sup> Professional 53949 PV2 matt gaffer tape

**Product Information** 

### **Additional Information**

Complies with LV 312-1 Dialectric strength.

#### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



<sup>2</sup>age 2 of 2 – as of 05/06/25 – en-SG