



# tesa<sup>®</sup> 58316

## Product Information



33 µm PCR-PET tape for In-Cell applications

### Product Description

tesa<sup>®</sup> 58316 is a 33 µm PCR-PET tape with an acrylic adhesive. tesa<sup>®</sup> 58316 has been designed for applications inside of EV battery cells.

### Sustainable Aspects



For more information: <https://www.tesa.com/product-sustainability>

### Product Features

- Electrolyte Resistance
- Laser Printability

### Application Fields

- Jelly-Roll Fixation
- Stack Fixation
- Welding-Seam Protection
- Cell-Tab Protection

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                                                         |                            |                    |         |
|---------------------------------------------------------|----------------------------|--------------------|---------|
| • Backing                                               | Post consumer recycled PET | • Type of adhesive | acrylic |
| • Bio-based carbon content of liner (acc. DIN EN 16640) | 90 %                       | • Total thickness  | 33 µm   |

### Properties/Performance Values

- |                       |         |                          |     |
|-----------------------|---------|--------------------------|-----|
| • Elongation at break | 100 %   | • Electrolyte resistance | yes |
| • Tensile strength    | 40 N/cm |                          |     |

### Adhesion to Values

- |         |          |
|---------|----------|
| • Steel | 1.9 N/cm |
|---------|----------|

For latest information on this product please visit <http://l.tesa.com/?ip=58316>



# tesa® 58316

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=58316>