

# tesa® 51608

## PV6



### Product Information

Double layer PET fleece sleeve for enhanced harness flexibility in the automotive passenger compartment

### Product Description

tesa® 51608 PV6 is a double layer PET fleece wire harness sleeve with a rubber-based adhesive. It combines good noise damping and abrasion resistance features with high flexibility.

tesa® 51608 PV6 is specifically designed for easy and efficient lengthwise application. Customized length-specific perforation for fast and clean tearing is available on request.

### Product Features

- High flexibility
- Noise damping
- Easy and efficient lengthwise application
- Adhesive-to-adhesive closure system
- Secure bonding without additional spot wraps
- Strong adhesion
- Ageing-resistant
- Flexible and smooth

### Application Fields

tesa® 51608 PV6 has been developed for bundling passenger compartment wire harness areas subject to high requirements for both noise damping and harness flexibility.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing	PET fleece	• Total thickness	560 µm
• Type of adhesive	rubber based		

### Properties/Performance Values

• Abrasion resistance (10mm mandrel, LV312)	Class B	• Temperature resistance max.	105 °C
• Abrasion resistance (5mm mandrel, LV312)	Class B	• Temperature resistance min.	-40 °C
• Noise damping (LV312)	Class D		

# tesa® 51608

## PV6

### Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51608PV6>