


tesa® 60571

Product Information



50µm double sided black electrically conductive non-woven tape

Product Description

tesa® 60571 is a black double sided electrically conductive self adhesive tape. It consists of an electrically conductive non-woven backing and an electrically conductive acrylic adhesive.

tesa® 60571 features especially:

- Excellent electrical conductivity in XYZ-direction even at high temperatures and humidity
- Good adhesion level even at harsh environmental conditions
- Excellent conformability and adjustment to uneven surfaces

Application Fields

- EMC applications, such as grounding and shielding

* Electrostatic discharge applications

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	conductive non-woven	• Color	black
• Type of adhesive	conductive acrylic	• Color of liner	transparent
• Type of liner	PET	• Thickness of liner	50 µm
• Total thickness	50 µm		

Properties/Performance Values

• Contact resistance z-direction (initial)	0.05 Ohm / square inch	• Static shear resistance at 40°C	good
• Release of liner	easy	• Surface resistance x-y-direction	0.3 Ohm / square
• Static shear resistance at 23°C	good	• Temperature resistance short term	180 °C

Adhesion to Values

• Steel (initial)	4 N/cm	• Steel (after 14 days)	5.4 N/cm
-------------------	--------	-------------------------	----------

tesa® 60571

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60571>