



tesa[®] PRO 74613

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	PE laminated cloth	• Type of adhesive	synthetic rubber
• Bio-based carbon content of liner (acc. DIN EN 16640)	63 %	• Total thickness	175 µm

Properties/Performance Values

• Elongation at break	18 %	• Hand tearability	good
• Tensile strength	41.5 N/cm	• Humidity resistance	yes
• Abrasion resistance	good	• Residue-free removability	no
• Adhesive strength	Standard adhesion	• Solvent free	yes
• Ageing resistance (UV)	medium	• Tear resistance	yes
• Chemical Resistance	medium		

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=74613>