

# tesa® 4244 PV0



## Product Information

Fineline tape for design painting

### Product Description

tesa® 4244 is a flexible soft PVC tape with a natural rubber adhesive for fineline masking if a very sharp paint edge is required, especially on painted or unpainted plastic parts and for multi-colour painting.

- no shrinking at high temperatures
- conforms to the dimensional change during oven-drying
- no edge lifting off and removable without leaving any residues
- good conformability to multi dimensional surfaces

### Application Fields

Masking & Design, for wide range of fineline applications

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                |                   |        |
|--------------------|----------------|-------------------|--------|
| • Backing          | PVC film       | • Total thickness | 110 µm |
| • Type of adhesive | natural rubber |                   |        |

### Properties/Performance Values

- |                    |         |                            |           |
|--------------------|---------|----------------------------|-----------|
| • Tensile strength | 27 N/cm | • Hand tearability         | very good |
| • Easy to remove   | yes     | • Suitable for die cutting | yes       |

### Adhesion to Values

- |         |          |
|---------|----------|
| • Steel | 3.7 N/cm |
|---------|----------|

### Additional Information

tesa® 4244 is also available for converting and die-cutting with a paper liner 4244 PV4:

adhesion to steel = 4,7 N/cm

peel off force from liner = 14 cN/cm,

die cuts are available as tesa® 54244

# tesa® 4244 PV0

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4244>