


tesa® 88720

Optically Clear Adhesive



Product Information

500µm Optically Clear Adhesive for Automotive Applications

Product Description

887xx Automotive OCA solution provides a wide thickness range together with outstanding ink step coverage feature and reliability performance.

It is a proven solution, well performed at glass/polarizer lamination stack-ups. And it would be suitable for a large and curved display lamination.

Product Features

- PSA type
- High transmission and low haze
- Smooth and easy liner removal
- High bonding strength
- Balanced gap filling and converting performance
- Excellent temperature, humidity and UV resistance

Application Fields

- Automotive Display Lamination
- Curved Glass
- Other optical integration

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	none	• Color of liner	transparent
• Type of adhesive	acrylic	• Thickness of easy release liner	75 µm
• Type of liner	PET	• Thickness of tape	500 µm
• Color	transparent	• Thickness of tight release liner	100 µm

Properties/Performance Values

• Ageing resistance (UV)	good	• Release of liner - outside	easy
• Haze	0.001 %	• Tack	very good
• Humidity resistance	very good	• Temperature resistance long term	105 °C
• Refractive index	1.48	• Transmittance (380 - 780nm) >	99.5 %
• Release of liner - inside	tight		

tesa® 88720

Optically Clear Adhesive

Product Information

Adhesion to Values

- Glass (initial) 11 N/cm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=88720>