

tesa® 4216

Product Information



Application Fields

tesa® 4216 is suitable for various types of masking applications.

Example applications are:

- Two-tone painting at low temperatures or for wet-demasking in automotive paint shops
- Masking for highly visible edge lines
- Masking applications in narrow curves

To ensure the highest performance possible, our aim is to fully understand your application (including the substrates involved) in order to provide the right product recommendation.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------|--------|
| • Backing | PE film | • Total thickness | 105 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------|-----------|-----------------------------------|----------|
| • Tensile strength | 17.5 N/cm | • Suitable for die cutting | yes |
| • Easy to remove | yes | • Temperature resistance (60 min) | 80 °C |
| • Paint anchorage | no | • Thickness of masking coverage | _NULL µm |
| • Sharp color edge | very good | | |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 2.5 N/cm |
|---------|----------|

tesa[®] 4216

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4216>