

tesa® CaRes 51919

Product Information



Repulpable double-sided splicing tape

Product Description

tesa® CaRes 51919 is a double-sided repulpable tape consisting of a tissue paper backing and a modified water-soluble acrylic adhesive.

Color: Blue

Product Features

- Highest tack properties
- Excellent adhesion on coated and uncoated papers, e.g. functional barrier packaging papers
- Good shear strength
- Good repulpability (w/o liner) over full pH-range (pH3 –pH9)
- Paper from well-managed certified forests and other controlled sources

Application Fields

tesa® CaRes 51919 is particularly suitable for:

- Flying splice processes with critical adherence conditions
- Permanent overlapped splices
- Core starting
- Manual as well as automatic application

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------------------|---------------------|--------|
| • Backing | Paper | • Color | blue |
| • Type of adhesive | repulpable tackified acrylic | • Color of liner | white |
| • Type of liner | bi-siliconised paper | • Thickness of tape | 115 µm |

Product Assortment

- | | |
|---------------------|------|
| • Available formats | ROLL |
|---------------------|------|

tesa[®] CaRes 51919

Product Information

Properties/Performance Values

- | | | | |
|---------------------------|------|--------------------------|-----------|
| • Hand tearability | yes | • Tack | very good |
| • Static shear resistance | good | • Temperature resistance | good |

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51919>