

# tesa® 50555

## Product Information



### Product Description

tesa® 50555 is a flexible, high-temperature-resistant PVC fineline masking tape with an acrylic adhesive. It is engineered for 2-tone masking applications during OEM paint shop processes. The acrylic adhesive is a suitable alternative for very demanding paint systems, sensitive to ghosting or yellowing.

The soft PVC backing enables reliable application on narrow contours and curved surfaces.

To support efficient processing, both standardized and customized applicators are available.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |          |                   |        |
|--------------------|----------|-------------------|--------|
| • Backing          | PVC film | • Total thickness | 120 µm |
| • Type of adhesive | acrylic  |                   |        |

### Properties/Performance Values

- |                    |         |                                   |           |
|--------------------|---------|-----------------------------------|-----------|
| • Tensile strength | 30 N/cm | • Sharp color edge                | very good |
| • Easy to remove   | yes     | • Suitable for die cutting        | yes       |
| • Hand tearability | good    | • Temperature resistance (60 min) | 160 °C    |
| • Paint anchorage  | yes     |                                   |           |

### Adhesion to Values

- |         |          |
|---------|----------|
| • Steel | 1.8 N/cm |
|---------|----------|

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=50555>