



Product Information

Low temperature compatible tensilised non-staining strapping tape

Product Description

tesa® 64293 is a tensilised polypropylene strapping tape with a special natural rubber adhesive system.

tesa[®] 64293 features excellent low temperature compatibility. It provides a secure bond to various surfaces and can be removed without adhesive residue or delamination at low temperatures down to 5°C.

tesa® 64293 is specially designed for safe fixation of goods during all types of transports.

Application Fields

Closing, holding, securing and surface protection for all kinds of industries. For example, the appliance, office automation, furniture and metal industries.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Backing materialType of adhesive	MOPP natural rubber	Total thickness	72 µm	
Properties/Performance Values				
Elongation at breakTensile strength	30 % 150 N/cm	Residue free removal	Yes	

Adhesion to Values

• steel	2.6 N/cm
---------	----------

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.