




tesa® Bumperfilm 50560 PVO



Product Information

Temporary protection for freshly painted surfaces

Product Description

tesa® Bumperfilm 50560 is a premium grade self adhesive film that has been developed for the protection of delicate surfaces, e.g. painted bumper.

User benefits:

- Cost saving due to reduction in rectification and final repair
- Preserves the paint finish, up to 6 months storage outdoor
- No special equipment needed, ensuring simple, low cost application and removal processes
- Good adhesion to the range of paint finishes, even during transportation (tested at speeds higher than 160 km/h - 100 mph)
- Easy disposal. Both film and adhesive system are environmentally friendly

Application Fields

- Protection against dirt and scratches during assembly, transport and storage of painted plastic parts or / and painted metal surfaces

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|-------------------|-------|
| • Backing material | polyolefinic film | • Total thickness | 75 µm |
| • Type of adhesive | PIB | | |

Properties/Performance Values

- | | | | |
|----------------------------|-----------|-----------------------|-----------|
| • Easy to remove | yes | • Tensile strength | 16 N/cm |
| • Suitable for die cutting | yes | • Chemical resistance | very good |
| • UV-resistance | 24 week/s | | |



tesa[®] Bumperfilm 50560 PV0

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=50560>