




tesa[®] 50600 Standard



Product Information

Green polyester/silicone masking tape

Product Description

tesa[®] 50600 is a green, high-temperature masking tape featuring a polyester backing with a silicone adhesive. Features and benefits include:

- Easy to apply
- High temperature resistance - up to 220°C / 428°F (30min.)
- One piece removal without leaving residues

Application Fields

Masking off areas not to be coated during powder coating process.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------|-------------------|-------|
| • Backing material | PETP | • Total thickness | 80 µm |
| • Type of adhesive | silicone | | |

Properties/Performance Values

- | | | | |
|--------------------------|--------|--------------------|---------|
| • Easy to remove | Yes | • Tensile strength | 75 N/cm |
| • Temperature resistance | 220 °C | • Hand tearability | low |
| • Elongation at break | 110 % | | |

Adhesion to Values

- | | |
|---------|--------|
| • steel | 4 N/cm |
|---------|--------|



tesa[®] 50600 Standard

Product Information

Additional Information

tesa[®] 50600 is also available on a special PET liner.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=50600>