tesa® 51432

Product Information

Extra strong bandoliering tape for heavy components

Product Description

For storage- and sequenzer-bandoliering in combination with crêped bandoliering tape.

Application Fields

The dimensionally stable smooth paper backing makes the product particularly suitable for bandoliering of heavy components.

Especially for sequenzer bandoliering, where more rigid belts are needed.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Backing material: flat paper
- Type of adhesive: natural rubber
- Total thickness: 330 µm

Properties/Performance Values

- Elongation at break: 6 %
- Tensile strength: 93 N/cm
- Temperature resistance: 100 °C

Adhesion to Values

- steel: 8 N/cm

For latest information on this product please visit http://l.tesa.com/?ip=51432

tesa® 51432

Product Information

Additional Information

tesa® 51432 may be combined with tesa® 51300 or 51316.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit http://l.tesa.com/?ip=51432