



# tesa<sup>®</sup> 4671

## Product Information



Acrylic coated colored cloth tape

### Product Description

tesa<sup>®</sup> 4671 is a strong acrylic coated cloth tape. It is based on a 120 mesh woven rayon fabric backing and a natural rubber adhesive.

tesa<sup>®</sup> 4671 is the premium gaffer tape in the assortment for "Arts & Entertainment" applications. .

Features:

- high adhesion even on rough surfaces
- excellent tensile strength
- can be written on
- conformable
- easy to remove without residues
- no unpleasant smell
- very matt surfaces for black and fluorescent colors
- can be removed without leaving any residues from almost any surface
- available in 11 colors: black, white, grey, red, blue, green, yellow. The product also comes in four special fluorescent colors: pink, orange, yellow, and green.

### Application Fields

- Bundling and reinforcing of heavy pipes, profiles etc
- Floor marking
- Fixation of carpets during exhibitions
- Securing of sharp edges
- Sealing of tins and tubes
- Sandblasting
- Floor coating
- ... and a lot more!

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                      |                   |        |
|--------------------|----------------------|-------------------|--------|
| • Backing material | Acrylic-coated cloth | • Total thickness | 280 µm |
| • Type of adhesive | natural rubber       |                   |        |

For latest information on this product please visit <http://l.tesa.com/?ip=04671>



# tesa<sup>®</sup> 4671

## Product Information

### Properties/Performance Values

• Elongation at break	9 %	• Mesh	120 per square inch
• Tensile strength	70 N/cm	• Straight tear edges	very good
• Abrasion resistance	very good	• Temperature resistance	140 °C
• Easy to write on	yes	(removability from aluminum after 30 min exposure)	
• Hand tearability	very good	• Water resistance	good

### Adhesion to Values

- steel 3.5 N/cm

### Additional Information

Recommendation: please conduct a test on the application surface before using the product.

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04671>