

tesa® 54400

product information



Precision die-cuts for temporary hole covering applications

tesa® 54400 die-cuts consist of a white polyethylene fleece, coated with a removable synthetic adhesive.

Main Application

Due to the specific shrinkage property of the fleece, tesa® 54400 die-cuts are suitable for hole covering applications before PVC underbody coating. At higher temperatures the die-cut begins to shrink and will fall off the substrate after a given time.

The die-cuts can also be used for marking and protection applications in production control, logistics and transport, where residue-free removal is required.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

• Backing material	fleece	• Type of liner	glassine
• Color	white	• Colour of liner	brown
• Total thickness	170 µm	• Weight of liner	90 g/m ²

Adhesion to

• Steel (initial)	2.5 N/cm
-------------------	----------

Properties

• Suitable for die cutting	Yes	• Conformability	●●●
----------------------------	-----	------------------	-----

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Additional Information

The die-cuts are supplied according to customer requirements in either roll form or as sheets.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=54400>