

# tesa® 51575

## **Product Information**



## Double-sided non-woven tape

## **Product Description**

tesa® 51575 is a double-sided tape with a non-woven backing. It is coated with a water-borne acrylic adhesive offering high tack and high shear and temperature resistance. The special adhesive formulation ensures a good bond even on rough surfaces like cardboard and corrugated board.

## **Application Fields**

General purpose mounting

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

<ul> <li>Type of liner</li> </ul>	glassine	<ul> <li>Type of adhesive</li> </ul>	water-based acrylic
<ul> <li>Weight of liner</li> </ul>	82 g/m <sup>2</sup>	<ul> <li>Total thickness</li> </ul>	90 μm
Backing material	non-woven	<ul> <li>Color</li> </ul>	translucent,
			transparent, optically

clear

#### Adhesion to Values

• Steel (initial) 3.2 N/cm

#### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.