

Product Information

Card Labels

tesa® 62019 consists of a double-sided polyester film with a pressure-sensitive, acrylic-based adhesive. One side of the label is made of a permanent adhesive that ensures a secure bond to paper. The other side is made of a non-permanent pressure-sensitive adhesive for the secure attachment of plastic cards. UV-fluorescent pigments make sensoric detection possible.

Features:

- Easily removable without leaving residues or damaging the card
- High adhesive reliability to all card surfaces and materials
- High processing reliability
- UV pigments enable the sensory label detection

Main Application

Mailing of cards

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

- | | | | |
|--------------------------------------|-------------------------------|--------------------------------------|------------------|
| • Adhesion to Steel (removable side) | 0.3 N/cm | • Type of adhesive | modified acrylic |
| • Backing material | PETP | • Adhesion to Steel (permanent side) | 4 N/cm |
| • Color | transparent with UV-particles | • Type of liner | glassine |
| • Total thickness | 120 µm | | |

Properties

- | | |
|------------------------|-----|
| • Residue free removal | Yes |
|------------------------|-----|

Additional Information

Standard version is PV3.

Label format: 38mm x 13mm

Labels/roll: 5000 pcs.

tesa® 62019

Product Information



Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=62019>