



tesa[®] 54221

Precision Die Cuts

Product Information

Premium self-adhesive felt for demanding BSR applications

Product Features

- Excellent noise damping properties
- Abrasion resistance
- High conformability
- High adhesive power
- Very good vibration absorbance
- Ageing resistance
- Does not ignite

Product Description

tesa[®] 54221 is a black, 2.1mm thick felt with high adhesive power. It combines high conformability with excellent noise damping properties.

Features:

- Excellent noise damping properties
- Abrasion resistance
- High conformability
- High adhesive power
- Very good vibration absorbance
- Ageing resistance
- Does not ignite

Application Fields

- Highest requirements for sound damping
- Vibration isolation
- Cushioning components
- Demanding bonding areas e.g. curved 3D surfaces
- Bridging larger gaps

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Properties/Performance Values

- | | | | |
|-----------------------|------|-----------------------|--------|
| • Elongation at break | 45 % | • Humidity resistance | medium |
|-----------------------|------|-----------------------|--------|

For latest information on this product please visit
<http://l.tesa.com/?ip=54221>



tesa® 54221 Precision Die Cuts

Product Information

Additional Information

Sound dampening properties and abrasion resistance are measured according to LV 312.

tesa® 54221 can be supplied individually to customer specification in various dimensions. Under the product number tesa® 60421, the material is also available as customized rolls.

Further material options:

tesa® 54211, 1.1mm, Grammage 160g/m²

tesa® 54236, 3.6mm, Grammage 600g/m²

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=54221>