

# tesa® 60608

## PV1



### product information

Premium self-adhesive PET fleece for demanding BSR applications

tesa® 60608 is a thin, black PET fleece with high adhesive power and high conformability. The product is optimized for noise prevention in the automotive industry.

Features:

- Good noise damping properties
- Abrasion resistance
- Smooth and flexible
- High adhesive power
- Good ageing resistance
- Self extinguishing (tested as composite with a non-inflammable material)

### Main Application

- Noise prevention and sound damping
- Cushioning components
- Reduction of friction between adjoining components
- Bridging small gaps

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Technical Data

• Backing material	PET fleece	• Elongation at break	17 %
• Color	black	• Tensile strength	37 N/cm
• Total thickness	250 µm	• Type of liner	glassine
• Type of adhesive	tackified acrylic	• Colour of liner	brown/blue logo

#### Adhesion to

- PE (initial) 3.3 N/cm

#### Properties

- |                            |     |                  |      |
|----------------------------|-----|------------------|------|
| • Suitable for die cutting | Yes | • Conformability | ●●●● |
| • Abrasion resistance      | ●●  | • Noise damping  | ●●●  |

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

#### Additional Information

Sound dampening properties and abrasion resistance are measured according to LV 312.

tesa® 60608 can be supplied individually to customer specification in various dimensions. Under the product number tesa® 54508, the material is also available as customized die cut.

For latest information on this product please visit  
<http://l.tesa.com/?ip=60608>

# tesa® 60608 PV1

## product information



### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=60608>