



tesa[®] 54338

Product Information



Precision die-cuts for permanent hole covering applications

Product Description

tesa[®] 54338 die cuts from strong polyester tape are suitable for permanent exterior and interior Hole Covering applications in automotive.

Die cuts are supplied on a white glassine liner. The liner is approved for paint applications.

Application Fields

This polyester tape is suitable for all PVC or paint oven drying processes up to 200 °C.

After electrophoretic painting where good compatibility and anchoring force to UBS (PVC) and sealant is required, e.g. car body platform, wheel houses, engine compartment.

Before paint shop where good paint compatibility is essential, e.g. A/B- pillar, sills, trunk.

At assembly line for exterior and interior Hole Covering on all car body areas.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Type of liner	glassine	• Total thickness	95 µm
• Backing material	PET film	• Color	transparent, optically clear
• Type of adhesive	modified acrylic, advanced acrylic		

Properties/Performance Values

• Temperature resistance (30 min)	160 °C	• Chemical resistance	very good
-----------------------------------	--------	-----------------------	-----------

Additional Information

We would like to recommend our stock assortment, which includes the following dimensions:

circles: 19 / 30 / 40 / 50 mm diameter

tesa[®] 54338 is available upon request in customer specific dimensions and can be delivered in either roll form or as sheets.



tesa[®] 54338

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=54338>