




tesa® 60234

Product Information



55µm single sided matte black electrically conductive tape xyz-axis

Product Description

tesa® 60234 is a matte black single sided electrically conductive self adhesive tape.

It consists of a matte black electrically conductive fabric backing which is coated with black electrically conductive acrylic adhesive.

tesa® 60234 features especially:

- Thickness: 55µm
- Excellent electrical conductivity in XYZ-direction for very good grounding performance
- High adhesion level even at harsh environmental conditions avoids edge lifting
- Minimized curling for easy processing and lamination
- Matte black surface (low gloss) with anti-finger print and solvent resistant characteristic

Application Fields

- Edge wrapping and grounding of electronic components

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------------|----------------------|--------------------------|
| • Backing material | Black conductive fabric | • Color | matte black |
| • Type of adhesive | conductive acrylic | • Colour of liner | transparent, translucent |
| • Type of liner | PET | • Thickness of liner | 50 µm |
| • Total thickness | 55 µm | | |

Properties/Performance Values

- | | | | |
|--|------------------------|---|------------------|
| • Contact resistance z-direction (initial) | 0.05 Ohm / square inch | • Surface resistance x-y-direction (adhesive) | 0.2 Ohm / square |
| • Static shear resistance at 23°C | good | • Surface resistance x-y-direction (backing) | 0.3 Ohm / square |
| • Static shear resistance at 40°C | good | • Temperature resistance short term | 200 °C |

Adhesion to Values

- Steel (after 14 days) 6.5 N/cm

For latest information on this product please visit <http://l.tesa.com/?ip=60234>



tesa[®] 60234

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60234>