



Product Information



High temperature PET masking film

Product Description

tesa® 51108 combines a polyester backing and a thermosetting adhesive to reach the optimal performance for high quality paint jobs.

The temperature resistance and the high tensile strength of 51108 provide an ideal usage for two-tone painting on body, especially if long straight lines are required.

- the PET-Film allows a tear-free removal after drying
- removable without leaving any residues

Application Fields

Masking & Design, for a wide range of fineline applications

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Backing materialType of adhesive	PET film natural rubber	Total thickness	54 µm
Properties/Performance Values			
Easy to removeSuitable for die cutting	Yes Yes	Temperature resistanceTensile strength	150 °C 47 N/cm

Adhesion to Values

• steel 3.3 N/cm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.