



tesa[®] 7140 PV3



Product Information

Flange masking tape in the automotive industry

Product Description

tesa[®] 7140 is a laminate of a PVC film and a PET film, thus providing both durability and high tensile strength. When bonding different types of surfaces (glass, metal, plastics), clearly defined surface properties are essential for reliable adhesion. Masking flange areas prior to paint processes is best practice to enable the later on applied adhesive to bond directly to the e-coated surface, thus ensuring bonding reliability and eliminating the need for additional surface treatment steps.

tesa[®] 7140 is compatible with common e-coats/fillers and structural liquid adhesives.

Application Fields

Masking tape for flange masking applications

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing material | PVC film | • Total thickness | 181 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|--------------------------|--------|--------------------|----------|
| • Easy to remove | Yes | • Tensile strength | 100 N/cm |
| • Temperature resistance | 170 °C | | |

Adhesion to Values

- | | |
|---------|--------|
| • steel | 4 N/cm |
|---------|--------|



tesa[®] 7140 PV3

Product Information

Additional Information

The product design of tesa[®] 7140 allows for both manual and automatic (robot) application and is also suitable for converting and die-cutting. In case of fully automatic applications the best-before-date of spools is 12 months under recommended storage conditions.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=07140>