

tesa® Edge Securing 50533

Product Information



High adhesion temporary protection tape for freshly painted surfaces

Product Description

tesa® Edge Securing 50533 consists of an UV-stabilized backing coated with a high adhesion EVA adhesive. Features & benefits:

- Paint protection during outdoor storage up to 12 months
- Secure adhesion during transport
- Easy disposal both the film and the adhesive system are environmentally friendly

Application Fields

- tesa® Edge Securing 50533 ensures high-strength adhesion and can be used to keep tesa Bodyguard® tapes securely in place, especially in areas of difficult geometries to prevent dust and humidity penentration
- tesa® Edge Securing 50533 is suitable for die-cutting and can be printed on to be used as security, steering or marking label
- tesa® Edge Securing 50533 can also be used as base material for heavy duty protection pads for bumpers and door edges

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing material	polyolefinic film	•	Total thickness	96 µm
•	Type of adhesive	EVA			

Properties/Performance Values

•	Easy to remove	Yes	•	Tensile strength	21.5 N/cm
•	Suitable for die cutting	Yes	•	Chemical resistance	very good
•	UV-resistance	52 weeks			



tesa® Edge Securing 50533

Product Information

Additional Information

tesa® Edge Securing 50533 is also available as die cut product solution as tesa® Edge Securing 54533.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.