



tesa® 60022

Product Information

Properties/Performance Values

• Resistance to chemicals	yes	• Temperature resistance min.	-30 °C
• Residue free removal	no	• Suitable surfaces	Even wood, Stone, Brick, Acrylic glass
• Waterproof	yes	• Adhesive strength	Light adhesion
• Solvent free	no	• Hazard material	yes
• Washable	no	• UV-resistant	yes
• Recommended distance of spraying	20 mm	• Temperature resistance	yes
• Suitable for children of 3 years of age	no	• Humidity resistance	yes
• Temperature resistance max.	80 °C		

Additional Information

- tesa offers two complementary Spray Glues: 60021 PERMANENT and 60023 REPOSITIONABLE
- Observe the safety-information on the spray-can
- Shake can well before use and remove any dried-on glue from the nozzle
- For new applications, test suitability by gluing a sample
- The parts to be bonded must be dry and free from dust and grease. We recommend cleaning with tesa® INDUSTRY CLEANER 60040
- After use, turn can upside-down and expel glue from nozzle until only propellant comes out
- Overspray from Spray Glues can easily be removed with tesa® 60042 ADHESIVE REMOVER
- Refer to special instructions/safety data sheets: www.tesa.com/safety

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=60022>