



# tesa® 60152

## Product Information



### Adhesion Promoter for PU

#### Product Description

tesa® Adhesion Promoter is used to improve the adhesion of tesa® ACX<sup>plus</sup> tapes on polyurethane and hard PVC. Due to the different behaviors of the substrates, we recommend to test our Adhesion Promoter prior to usage. tesa® Adhesion Promoter 60152 is UV traceable, because of UV pigments contained in the solution.

#### Application Fields

Recommended for PU and hard PVC.

Used to enhance the bonding strength and to reach higher peel adhesion values with our ACX<sup>plus</sup> tapes.

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Additional Information

The bonding surface should be free of dust, grease, oil, moisture and other contaminants before using tesa® Adhesion Promoter 60152.

Clean the substrate with a lint free cloth and appropriate solvents, such as Ethanol or Isopropanol.

Then apply tesa® Adhesion Promoter 60152 thinly to the bonding surface, making sure that the entire surface is coated.

The Adhesion Promoter can be applied with a lint free cloth or brush, application pen or felt applicator.

Wait 2 to 5 minutes to give the solvents time to evaporate.

Keep the prepared surface free from contaminants prior to applying tesa® ACX<sup>plus</sup> tape.

Open time for bonding are several hours/ days.

Shelf life are 12 month when stored in the original container at room temperature.

For all further information kindly refer to the respective material safety data sheet (MSDS).

<http://www.tesa.com/company/safety/msds>

For latest information on this product please visit <http://l.tesa.com/?ip=60152>



# tesa<sup>®</sup> 60152

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60152>