



tesa[®] 53128

Product Information

Standard Grade Paper Masking Tape

Product Description

tesa[®] 53128 PV8 is a thin and flexible standard grade masking tape with a yellow coloured crepe paper backing and a natural rubber adhesive. The masking tape is suitable for a wide range of general masking applications without or with subsequent oven-drying up to a temperature of 80°C/1h (Short term: 100°C / 0,5h). It can be also used in indoor painting applications up to 7 days.

The natural rubber adhesive provides a good adhesion to multiple surfaces, like metal, rubber, glass and plastic. The fine crepe paper backing is flexible and conformable and is easy to tear by hand. Paints and fillers adhere well to the reverse side, preventing any kind of flaking.

Application Fields

- tesa[®] 53128 PV8 is a flexible masking tape used for spray-painting, painting, and varnishing applications
- The masking tape has good holding power on various surfaces
- The tape is suitable for oven-drying with temperatures of up to 80°C/1h and 100°C/0,5h.
- Indoor painting

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|-------------------|--------|
| • Backing material | slightly-creped paper | • Total thickness | 140 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | |
|--------------------|---------|
| • Tensile strength | 32 N/cm |
|--------------------|---------|



tesa[®] 53128

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=53128>