



tesa® 60630

Product Information



30µm conformable aluminum foil tape

Product Description

tesa® 60630 is a conformable aluminum tape based on a 30 µm (1.2 mil) aluminum foil, a transparent acrylic adhesive.

Features:

- Conformable to curved surfaces
- Easy to unwind
- Suitable for permanent applications
- Barrier against moisture, gases and vapors
- Electrically and thermally conductive
- Aging resistant
- Heat and light reflective
- Flame retardant according to DIN 4102, class B1
- Flame retardant according to the requirements in UL 510A

Application Fields

- Mounting of refrigerator coils in appliance industry
- * Joining and sealing of thermal insulation and ducts
- * To make substrates electrically and thermally conductive
- * To reflect heat radiation

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|--------------------|---------|
| • Type of liner | none | • Type of adhesive | acrylic |
| • Backing material | aluminium foil | • Total thickness | 65 µm |

Properties/Performance Values

- | | | | |
|-------------------------------|------------|-------------------------------|-----------|
| • Easy to remove | no | • Hand tearability | very good |
| • Elongation at break | 3 % | • Operation temperature from | -40 °C |
| • Tensile strength | 25 N/cm | • Operation temperature up to | 160 °C |
| • Backing appearance (visual) | reflective | | |

For latest information on this product please visit <http://l.tesa.com/?ip=60630>



tesa[®] 60630

Product Information

Adhesion to Values

• Backing	0.1 N/cm	• PVC (initial)	5.5 N/cm
• Glass (initial)	7 N/cm	• steel	8 N/cm
• PE (initial)	4 N/cm		

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=60630>