

# 60652



## Product Information

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Technical Data

• Backing material	aluminium foil	• Thickness of liner	85 µm
• Total thickness	90 µm	• Release of liner	easy
• Type of adhesive	acrylic	• Temperature resistance min.	-40 °C
• Elongation at break	6 %	• Temperature resistance max.	160 °C
• Tensile strength	40 N/cm	• Surface finish	reflective

#### Adhesion to

• steel	9.0 N/cm	• PE (initial)	4.5 N/cm
• Glass (initial)	9.0 N/cm	• PVC (initial)	6.0 N/cm

#### Properties

• Hand tearability	●●●●	• Abrasion resistance	●●●●
• Suitable for die cutting	Yes	• Water resistance	●●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=60652>