



tesa® 60009

Product Information



Super soft PVC closed cell single sided foam tape 9.5mm thick (grey)

Product Description

tesa 60009 is a 9.5mm thick super soft grade closed cell PVC foam tape with an acrylic adhesive on one side. The closed cell foam can create a water proof barrier when compressed, while the super soft grade foam construction remains extremely flexible and conformable to allow easy sealing of uneven surfaces. After long periods of compression, the foam will recover to its original state. tesa 600 Series foam tape is also resistant to fungi, oxidation and UV, making it suitable in tough conditions. tesa 600 Series foam tape is available in 3.2mm, 6.4mm, 9.5mm and 12.7mm thicknesses in the colour grey.

Application Fields

tesa 600 Series foam tape is ideal for use in recreational vehicles such as caravans and campervans, concreting and the construction of portable buildings, where uneven surfaces including corrugated sheeting require sealing.

Application ideas:

- * Sealing caravan panels
- * Dam wall sealing in concreting
- * Sealing panels on portable buildings
- * Sealing profiled and corrugated panels and cladding
- * Sealing around stainless steel sinks and hatchery doors

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Backing material PVC foam
- Type of adhesive acrylic

Properties/Performance Values

- Elongation at break 140 %
- Chemical resistance good
- Temperature resistance min. -40 °C

For latest information on this product please visit <http://l.tesa.com/?ip=60009>



tesa[®] 60009

Product Information

Adhesion to Values

- steel 2.8 N/cm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60009>