



tesa[®] 64432

Product Information



Premium Flatback Paper Splicing Tape

Product Description

tesa[®] 64432 is a single-sided flatback paper tape with a very strong natural rubber adhesive. Due to the tough backing and strong adhesive it is suitable for various applications such as splicing, low to medium grit blasting, belting and many more. The excellent visible blue colour of tesa[®] 64432 provides easy identification of splices.

Product Features

- The temperature resistance makes it suitable to perform even under higher temperatures.
- High adhesion on board and similar substrates
- High shear- and temperature resistance for reliable splices and PE-coating
- Blue color for easy and reliable splice detection
- Low unwinding force for easy application

Application Fields

- tesa[®] 64432 is recommended for splicing of various kind of materials
- The flatback paper tape can be used as stencil material for low medium grit blasting
- tesa[®] 64432 is suitable as splinter protection tape for indoor mirrors

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing material | flat paper | • Total thickness | 300 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|----------|--------------------|------|
| • Elongation at break | 7 % | • Hand tearability | good |
| • Tensile strength | 106 N/cm | | |

Adhesion to Values

- | | |
|---------|--------|
| • steel | 7 N/cm |
|---------|--------|



tesa[®] 64432

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=64432>