



tesa® 61332

Product Information

tesa® 61332 double-sided self-adhesive tape

Product Features

- Thickness: 200µm
- Very good bonding strength
- Superior push-out resistance
- Easy handling and process performance due to very strong PET backing
- White color for easy detection or design purposes

tesa® 61332 is a double sided self-adhesive tape consisting of a white PET film backing and a tackified acrylic adhesive.

Special features:

- Thickness: 200µm
- Very good bonding strength
- Superior push-out resistance
- Easy handling and process performance due to very strong PET backing
- White color for easy detection or design purposes

Product Construction

• Type of adhesive	tackified acrylic	• Total thickness	200 µm
• Type of liner	glassine	• Thickness of liner	71 µm
• Colour of liner	white/red logo	• Backing material	PET film
• Weight of liner	80 g/m ²	• Color	white

Product Properties/Performance Values

• Elongation at break	80 %	• Tensile strength	130 N/cm
• Static shear resistance at 23°C	very good	• Ageing resistance (UV)	very good
• Humidity resistance	++	• Static shear resistance at 40°C	very good
• Tack	low	•	-40 °C

Adhesion to Values

• Steel (initial)	17.8 N/cm	• Glass (after 14 days)	17.3 N/cm
• PC (after 14 days)	18.4 N/cm	• Glass (initial)	16.1 N/cm
• Steel (initial)	17.8 N/cm	• Steel (after 14 days)	19.8 N/cm
• PC (initial)	14 N/cm		



tesa® 61332

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=61332>