



# tesa® Softprint 72228

## Product Information



Foam plate mounting tape: CLASSIC product design

### Product Description

Double-sided foam tape.

#### Foam properties

- Low thickness tolerance
- Long lasting, constant recovery characteristics

#### Adhesive properties

- Medium tack surface characteristics
- Sufficient plate bonding
- Easy plate demounting
- Fair tape bonding towards sleeve side

#### Additional property

- Structured PP-liner to prevent formation of air pockets when the plate is mounted

### Application Fields

Mounting of 1,14 mm (0,045") and 1,70 mm (0,067") flexographic printing plates onto PU and glassine cylinders.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                              |                    |                   |
|--------------------|------------------------------|--------------------|-------------------|
| • Type of liner    | PP                           | • Type of adhesive | tackified acrylic |
| • Backing material | PE foam with film lamination | • Total thickness  | 550 µm            |

### Properties/Performance Values

- |                 |       |                      |     |
|-----------------|-------|----------------------|-----|
| • Color of logo | green | • Thickness category | 500 |
| • Hardness      | hard  |                      |     |



# tesa<sup>®</sup> Softprint 72228

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=72228>