



Product Information

Surface protection tape

tesa® 54889 combines a strong polyester backing with a powerful acrylic adhesive. The PET layer serves as an excellent barrier against steam and vapor, protecting the surface which the die cut is adhered to. tesa® 54889 is used in the appliance industry and is especially suited for protecting countertops from the steam and vapor produced by dishwashers and ovens.

Benefits:

- Excellent protection of the surface from vapor and steam
- · High transparency for a secure and subtle application
- · Secure adhesion to various materials

Main Application

• tesa® 54889 is used in the appliance industry and is especially suited for protecting countertops from the steam and vapor produced by dishwashers and ovens.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

| Backing material | PET film | Type of adhesive | modified acrylic |
|---------------------------------------|----------|--|------------------|
| Total thickness | 236 μm | Thickness of liner | 36 μm |
| Thickness of tape | 200 um | | |

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

