



tesa® Professional 4344 Precision Mask® Standard



Product Information

High grade paper masking tape for precise and flat paint edges

Product Description

tesa® 4344 Precision Mask® consists of an extra-thin and strong paper backing coated with an acrylic adhesive.

The combination of the highly equipped backing material and the outstanding special adhesive formulation allows easy removability up to 5 months after application, with 4 weeks of UV resistance. This enables multiple working processes in only one covering process.

Application Fields

This tape is suited for almost all indoor paint works.

tesa® 4344 Precision Mask® is applicable with water-based paints and lacquers and fits even for high-class spatula techniques.

It is suitable for a variety of common surfaces such as glass, aluminium, hard-PVC and wood.

It is especially suited for indoor applications when a precise razor-sharp paint edge is needed.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------|-------------------|-------|
| • Backing material | Washi paper | • Total thickness | 90 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|--------------------|-----------|
| • UV-resistance | 4 weeks | • Tensile strength | 30 N/cm |
| • Elongation at break | 4 % | • Hand tearability | very good |

Adhesion to Values

- | | |
|---------|----------|
| • steel | 1.7 N/cm |
|---------|----------|



tesa[®] Professional 4344 Precision Mask[®] Standard

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=04344>