




tesa® Softprint 74524

Product Information



Foam plate mounting tape

Product Description

Double-sided foam plate mounting tape for reverse mounting application.

First the tape is applied to the plate. Then the liner of the tape is removed and plate and tape are mounted on the cylinder/ sleeve.

Foam properties

- Low thickness tolerance
- Long lasting, constant recovery characteristics
- FLEX product design compensates for irregular bonding surfaces

Adhesive properties

- Low tack surface characteristics (plate side adhesive) for easy repositioning and mounting
- High plate bonding
- High tape bonding towards sleeve side
- Easy plate demounting

Additional property

- Structured PP-liner to prevent formation of air pockets when the plate is mounted

Application Fields

Mounting of 1,14 mm (0,045") and 1,70 mm (0,067") flexographic printing plates onto steel /alu /PU sleeves/cylinders

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------------------|-------------------|--------|
| • Backing material | PE foam with film lamination | • Type of liner | PP |
| • Type of adhesive | tackified acrylic | • Total thickness | 550 µm |

Properties/Performance Values

- | | | | |
|-----------------|--------|----------------------|-----|
| • Hardness | medium | • Thickness category | 500 |
| • Color of logo | purple | | |



tesa[®] Softprint 74524

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=74524>