

# tesa® Softprint 72322

**Product Information** 



Foam plate mounting tape: CLASSIC product design

#### **Product Description**

Double-sided foam tape

#### Foam properties

- Low thickness tolerance
- Long lasting, constant recovery characteristics

#### Adhesive properties

- Medium tack surface characteristics
- Sufficient plate bonding
- Easy plate demounting
- Excellent tape bonding towards sleeve side

Additional property

• Structured PP-liner to prevent formation of air pockets when the plate is mounted

## **Application Fields**

Mounting of 1,14 mm (0,045") and 1,70 mm (0,067") flexographic printing plates onto steel /alu /PU and glassine cylinders

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

Backing material	PE foam with film • lamination •	Type of liner Total thickness	PP 550 μm					
• Type of adhesive	tackified acrylic, acrylic, advanced acrylic, modified acrylic							
Properties/Performance Values								

٠	Hardness	soft	•	Thickness category	500
٠	Color of logo	red			



## tesa® Softprint 72322

**Product Information** 

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 - as of 25/02/23 - en-SG