

tesa Sleeve® 51608 PV8



Product Information

PET fleece Sleeve for enhanced flexibility

tesa Sleeve® 51608 PV8 is a PET fleece coated at the edges with rubber based adhesive for lengthwise application.

Major Features:

- High flexibility
- Noise damping
- Easy and efficient lengthwise application

Color: Black

Main Application

tesa Sleeve® 51608 PV8 is designed for the passenger compartment, providing high flexibility. For lengthwise application

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

• Backing material	PET fleece	• Abrasion resistance (10mm mandrel)	Class A (acc. to LV312)
• Total thickness	210 µm	• Abrasion resistance (5mm mandrel)	Class A (acc. to LV312)
• Type of adhesive	rubber based	• Flame resistance as composite	Class B (acc. to LV312)
• Temperature resistance min.	-40 °C	• Noise damping (decibel)	Class C (acc. to LV312)
• Temperature resistance (3000h)	105 °C		

Adhesion to

- steel 3.0 N/cm

Additional Information

Standard widths: 80, 100, 130, 180, 250 mm

Standard lengths: 50 m

- Most combinations of width and length are possible
- Also available with customized perforation

Harness diameter / tesa Sleeve® width recommendation

< Ø 18 mm / 80 mm > Ø 18 mm – 24 mm / 100 mm

Ø 24 mm – 33 mm / 130 mm

Ø 33 mm – 49 mm / 180 mm

Ø 49 mm – 72 mm / 250 mm

- Standard core diameter: 76 mm

For latest information on this product please visit
<http://l.tesa.com/?ip=51608>

tesa Sleeve® 51608 PV8



Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=51608>