

tesa® 4435



Product Information

UV Paper Masking Tape

tesa® 4435 UV Paper Tape is applicable with all kind of paints. The combination of the conformable backing material and the special adhesive formulation allows easy residue free removability up to 2 weeks after outdoor application. This enables multiple working processes in only one covering process.

Main Application

This tape is suited for almost all outdoor paint works. It is suitable for outdoor applications on a variety of common surfaces.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

• Total thickness	145 µm	• Tensile strength	38 N/cm
• Type of adhesive	natural rubber	• UV-resistance	2 weeks
• Elongation at break	12 %		

Adhesion to

• steel	2.8 N/cm
---------	----------

Properties

• Hand tearability	●●●	• Paint anchorage	●●●●
• Suitable for rough surfaces	●●●	• Conformability	●●●

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

Additional Information

The application of an adhesive tape on weathered surfaces may lead to residues during the de-masking. Therefore we strongly recommend a test application before.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=04435>