

A woman is the central figure, smiling broadly while taking a selfie with her smartphone. She is wearing a black mountain bike helmet, a bright yellow high-visibility jacket with reflective strips, and black gloves. A backpack is visible behind her. The background is a blurred mountain landscape under a clear sky.

Adhesive solutions

Enabling the future of the electronics industry 2022

At the bottom of the page, there are two horizontal bars: a red one on the left and a blue one on the right, both extending across the width of the page.

About us



Qualified experience and individual support

As a leading adhesive manufacturer in the electronics industry, we offer a wide range of customized adhesive tapes for smartphones, tablets, and other electronic devices. We work continuously to develop new products to better serve you and your customers in this fast-moving and innovative industry.

You and your suppliers are our priority. Our team of experts – from sales offices, R&D centers, and manufacturing facilities – is available globally to support our customers locally. Particularly, our Customer Solution Center with its technical experts is there to offer you the individual support you need. Our state-of-the-art facility with extensive equipment is at your disposal to find the adhesive solution for your needs.

Contents

	Page
Introduction	
Your complete partner	4
Tapes for your success	5
Our commitment to sustainability	6–7
Mounting solutions	
Double-sided film tapes	8
High performance profile	8–9
Specialized performance profile	10–11
Well-balanced performance profile	12–13
Impact-resistant foam tapes	14
Acrylic foam tapes	14–15
PE foam tapes	16–17
Special foam tapes	18–19
Bond & Detach®	20
Stretch-release tapes	20–21
Structural bonding solutions	22
Heat-activated films	22–23
Low-temperature reactive films	22–23
Functional solutions	
Electrically conductive solutions	24
Double-sided electrically conductive tapes	24–25
Single-sided electrically conductive tapes	26–27
Single-sided electrically conductive foam tapes	28–29
Thermal management tapes	30
Thermal management tapes	30–31
Covering tapes	32
Covering tapes	32–33
Display lamination solutions	
Optically clear adhesive tapes	34
Optically clear adhesive tapes	34–37
Global presence – Contacts	38

Your complete partner


Solutions that go beyond tape

Every project comes with new and individual challenges. We overcome these challenges by partnering with you to create unique and specialized products that meet and exceed your customers' expectations. Our capability goes beyond tape, as we also offer a comprehensive technical product package.



Our labs and technical experts

With our extensive experience in adhesive technology, we have developed a large portfolio of adhesive products for electronics applications. Our technical experts will support you throughout your entire product development process and help you find the optimal solution for your requirements.



On-site support

We provide individual project support backed up by application engineers and research and development resources. Our technical experts in our Customer Solution Center offer on-site support and evaluation of your individual application under laboratory conditions.



Contact us


Our local experts and engineers are just a phone call away to support you with:

- Process-simulation studies
- Assistance at your manufacturing site
- State-of-the-art testing equipment
- Tests under a wide range of environmental conditions
- Customized tests with customer substrates

Contact us and benefit from a strong partnership.

Tapes for your success

Solutions that meet your needs



Tape solutions for smartphones

Our products have a proven track record in multiple applications and different devices over the last 20 years in the electronics industry. In this brochure we present an assortment of the most significant tapes from our portfolio. We divide them into the following categories:

- **Mounting Solutions**
- **Functional Solutions**
- **Display Lamination Solutions**

As each project has specific requirements, we offer tailored solutions to each application. Our mission is to provide you with the best solution. Please contact our local representative to discuss this in detail.

Features of our tapes

 Bonding performance	 Impact resistance	 Residue-free removal	 Anti-repulsion	 LSE performance	 Reliability	 Chemical resistance
 Conformability	 Electrical conductivity	 Thermal management	 Moisture blocking	 Outgassing resistance	... and many more	

Our commitment to sustainability

Just like us, many of our customers are committed to achieving greater sustainability. We support them by enabling them to make technological progress and actively contribute to sustainability through our products.



“Electronic equipment is complex. Intelligent solutions are necessary in order to make it more sustainable – for instance, in order to improve its recyclability. At tesa, we are aiming to play a leading role in this process. Our “Bond & Detach®” products demonstrate what that means in practice. They make it possible to easily remove the individual components of a smartphone – either for repair purposes or at the end of the phone’s life – and to recycle them separately. At the same time, we would like to help extend the life of electronic equipment through our products so that items don’t have to be disposed of so quickly.”

Carsten Meyer-Rackwitz
Corporate Vice President Business Unit Electronics

Development of sustainable solutions

Reducing a product’s carbon footprint while maintaining the same level of quality is a core product development issue for us. In the future, we intend to use an increased volume of raw materials that are more environmentally and climate friendly than conventional raw materials. Here, we evaluate the use of different raw materials. In particular, the use of recycled and bio-based raw materials is currently a key concern for us.

For example, with our new bio-based PET tapes, which use 50% recycled materials for the PET backing and whose adhesive consists of more than 70% bio-based carbon content.

At the same time, we avoid scarce raw materials or raw materials whose extraction places an excessive burden on the environment. We are also looking to make further reductions in our use of solvents during the production process.



Smart products for sustainability

We aim to help our customers work toward a circular economy. Our tesa® Bond & Detach products, for example, assist with this process. If modern smartphones are no longer needed or are broken, it is generally difficult to take them apart. Our tesa® Bond & Detach products make it possible to

attach components such as batteries and many other parts so that they remain securely in place until the product life is over. They can then be removed without any difficulty and without leaving any residue. Electronic parts can thus be replaced, properly disposed of, or recycled.


Double-sided film tapes


High performance profile


Our high performance profile tapes are the spearhead of our film tapes assortment. All series in this category are characterized by superior bonding performance, which is expressed in peel adhesion, push-out and shear resistance,


and high impact resistance. These series are therefore used for demanding applications like lens and battery mounting. The PET backings used in these series are very well suited to being die-cut.

Features


High bonding


Push-out



Good die cutting


Impact resistance


Typical applications



Lens and touch-panel mounting






Battery mounting



Component mounting

Assortment overview

	tesa® 613xx	tesa® 618xx	tesa® 6896x
Design			
Color	Transparent, black	Black	Transparent
Adhesive	Tackified acrylic	Modified acrylic	Specialty
Backing	PET	PET	PET
Special features	Push-out resistance, strong bonding	Push-out resistance, impact resistance, LSE performance	Strong bonding, easy activation, LSE performance
Thickness	30 µm		○ 68960
	50 µm	○ 61305 ● 61350	○ 68962
	100 µm	○ 61360 ● 61365	○ 68964
	125 µm	○ 61370 ● 61375	
	150 µm	○ 61380 ● 61385	
	200 µm	○ 61390 ● 61395	
	230 µm	● 61345	
	250 µm	● 61325	
	300 µm	● 61315	
Product performance	Reference product	● 61365 ○ 61360	● 61865
	Peel adhesion [N/cm; initial/ultimate]	11.9/16.5	11.0/12.0
	Push-out [N]	250	240
	DuPont [J; xy/z]	0.5/0.2	0.7/0.3

○ Transparent ● Black

Double-sided film tapes

Specialized performance profile

With this assortment, we created double-sided mounting tapes with unique adhesives focusing on the special requirements of certain applications in the electronics industry. Each series within this assortment focuses on a specific

property needed in the market. In this section, you will find a selection of specialized film tapes. Our capabilities go beyond what is available here. Please contact our local representatives to discuss this further.

This assortment features

Anti-repulsion

Differential designs

LSE performance

Chemical resistance

Bio-based content

Impact resistance








Temperature resistance

Typical applications



Our specialized film tape solutions are suitable for applications with a high demand for a certain property like anti-repulsion, differential bonding performance, chemical resistance, reworkability, or light blocking. These tapes are suitable for a wide range of applications, from mounting (e.g., FPC, antenna, keypad, sensor) to processing and packaging applications.

Assortment overview

	tesa® 6693x	tesa® 615xx	tesa® 612xx/6128x	tesa® 6881x	tesa® 885x	tesa® 6887x 	
Design							
Color	Transparent	Transparent	Black	Black	Translucent	Transparent	
Adhesive	Tackified acrylic	Silicone/acrylic	Specialty	Tackified acrylic	Tackified acrylic	Bio-based acrylic	
Backing	PET	PET	PET	PET	Nonwoven	PCR PET	
Special features	Repulsion resistance, easy activation	Differential design for silicone substrates LSE performance	Chemical resistance, impact resistance	LSE performance, high tack, impact resistance	Temperature resistance	Bio-based PET solution, high bonding	
Thickness	30 µm	○ 66930	○ 61526		○ 8851	○ 68873	
	50 µm	○ 66932	○ 61532	● 61250/61282	○ 8853 ○ 8857	○ 68875	
	100 µm	○ 66934	○ 61528	● 61210/61284	○ 8854	○ 68877	
	140 µm		○ 61529				
	150 µm			● 61215/61286			
	200 µm		○ 61520	● 61220/61287	● 68817		
	250 µm			● 61225/61288			
Product performance	Reference product	○ 66934	○ 61528	● 61210	● 68814	○ 8854	○ 68877
	Peel adhesion [N/cm; initial/ultimate] SUS	10.7/11.6	Si: 4.0/4.4 Ac: 10.7/12.6	12.4/13.2	13.5/14.0	8.3/9.5	12.3/13.7
	Push-out [N]	143	Upon request	260	130	Upon request	Upon request
	DuPont [J; xy/z]	0.7/0.2	Upon request	1.1/0.7	0.9/0.4	Upon request	Upon request

○ Transparent ● Black ○ Translucent

○ Transparent ● Black ○ Translucent

Our sustainable solutions

We are continuously increasing our range of sustainable products to help our customers achieve their own sustainability goals. We are willing to offer products that have the lowest possible impact on the environment throughout their life cycle. The use of recycled and bio-based raw materials plays a particularly important role here. In our product development, we focus on the design and integration of various sustainable building blocks in order to provide our customers with the greatest possible flexibility in the selection of products. Reach out to us, learn more about this exciting development, and become part of it!



Double-sided film tapes

Well-balanced performance profile

tesa® balanced-performance film tapes are a proven solution for mounting and lamination applications in the electronics industry. The balanced adhesive provides very good tack and bonding performance for many general applications. The PET backing enables easy handling of the tape

during converting and manufacturing processes. With thicknesses from 5 µm to 250 µm, this assortment offers you a broad range and excellent flexibility.

Features





Balanced properties





Good die cutting

Typical applications



This assortment is widely used in the electronics industry for versatile mounting and lamination applications as well as for cushioning and gasket material bonding.

Assortment overview

	tesa® 49xx	tesa® 519xx
Design		
Color	Transparent	Black
Adhesive	Tackified acrylic	Tackified acrylic
Backing	PET	PET
Thickness	5 µm	○ 4912
	30 µm	○ 4983
	50 µm	○ 4972
	80 µm	○ 4980
	100 µm	○ 4982
	125 µm	○ 4928
	140 µm	○ 4942
	160 µm	○ 4967
	200 µm	○ 4965
	250 µm	○ 4926
Product performance	Reference product	○ 4982
	Peel adhesion [N/cm; initial/ultimate] SUS	11.0/11.7
	Push-out [N]	230
	DuPont [J; xy/z]	0.5/0.2

○ Transparent ● Black

Can't find the
right solution?

We have more options available in our portfolio, and by partnering with you we can create unique and specialized products that meet your individual demands. **Simply write to us or contact your local representative:**
electronics@tesa.com




Acrylic foam tapes


For applications with extreme requirements


Our acrylic foam tape assortment is especially designed for demanding applications in the electronics industry and is distinguished by its very special bonding capabilities. The high bonding performance is possible due to the tape’s viscoelasticity: elastic and viscous characteristics provide inner strength and relax mechanical stresses. The use of

highly innovative technologies and special acrylic adhesive systems together with the viscoelastic nature of acrylic foams create multiple benefits like impact resistance, high bonding strength, and waterproofing for electronic devices for the entire life cycle of the product.


Features


High bonding


Impact resistance


Water-proofing


Typical applications




Lens mounting



Back cover mounting








Display bottom



Mounting in wearables devices

Assortment overview

	tesa® 754xx/756xx	tesa® 759xx	tesa® 758xx	tesa® 757xx	tesa® 7017x	
Design						
Color	Black	Black	Black	Black, white	Black	
Adhesive	Modified acrylic	Acrylic	Acrylic	Modified acrylic	Modified acrylic	
Backing	-	PET	-	PET	PET	
Special features	Excellent bonding, conformability	Chemical resistance, reworkability	Chemical resistance, excellent shock resistance	Good wetting, reworkability	Anti-stretching, easy activation	
Thickness	50 µm	● 75405	● 75805			
	100 µm	● 75410	● 75810	● 75710		
	150 µm	● 75415	● 75815	● 75715 ○ 75742		
	200 µm	● 75620	● 75920	● 75720 ○ 75743	● 70172	
	250 µm	● 75625	● 75925	● 75725 ○ 75745		
	300 µm	● 75630	● 75930	● 75730	● 70174	
	350 µm	● 75635				
	400 µm	● 75640				
	450 µm	● 75645				
Product performance	Reference product	● 75620	● 75920	● 75820	● 75720	● 70172
	Peel adhesion [N/cm; initial/ultimate] SUS	11.2/17.0	10.2/11.3	8.5/9.6	12.3/13.5	14.0/15.0
	Push-out [N]	220	160	140	205	210
	DuPont [J; xy/z]	1.3/1.0	1.2/0.9	1.5/1.0	0.9/0.8	1.4/1.0
	Removability*	●	● ● ●	●	● ● ●	● ● ●

* Assessment is done only in relation to other products of this assortment

○ White ● Black

Your partner
for co-
development

We have more options available in our portfolio, and by partnering with you we can create unique and specialized products that meet your individual demands. Simply write to us or contact your local representative: electronics@tesa.com





PE foam tapes


For challenging applications

PE foam tapes have long proven their value to the electronics industry. Certain properties such as impact resistance, bonding strength, and waterproofing are offered by all series in our PE foam range. In this section we present a selection of our PE foam solutions focusing on different series’ specific performance features. We believe these functionalities are strongly needed in the market for certain applications. If you require more information than what we have provided here, please contact your local representative.

Features


High bonding


Impact resistance


water-proofing


Typical applications




Lens mounting



Back cover mounting









Camera lens mounting



Display bottom mounting

Assortment overview

	tesa® 666xx	tesa® 668xx	tesa® 6262x	tesa® 6264x	tesa® 6698x	tesa® 628xx		
Design								
Color	Black	Black, white	Black	Black	Black	Black		
Adhesive	Tackified acrylic	Modified acrylic	Tackified acrylic	Tackified acrylic	Acrylic	Tackified acrylic		
Backing	PE foam	PE foam	PE foam	PE foam with PET reinforcement	PE foam	PE foam		
Special features	Best shear resistance, repulsion resistance	Best impact resistance, repulsion resistance	Best bonding, conformability	Good die cuttability, balanced property profile	Chemical resistance, repulsion resistance	Best repulsion resistance		
Thickness	150 µm	● 66822						
	200 µm	● 66624	● 66824	● 62624	● 66984	● 62864		
	250 µm	● 66625	● 66825 ● 66865	● 62625	● 66985	● 62865		
	300 µm	● 66626	● 66826 ● 66866	● 62626	● 66986	● 62866		
	350 µm	● 66627	● 66829			● 62867		
	400 µm		● 66828					
Product performance	Reference product	● 66626	● 66826	● 62626	● 62646	● 66986	● 62866	
	Peel adhesion [N/cm; initial/ultimate]	SUS	10.0/12.2	12.5/14.5	13.0/16.0	10.0/13.5	7.8/8.5	7.6/11.5
		PC	11.0/14.3	12.5/16.0	15.0/16.0	11.0/15.5	9.2/15.5	4.8/10.9
	Push-out [N]		248	252	180	180	252	226
	DuPont [J; xy/z]		0.85/0.74	0.88/0.77	0.48/0.42	0.45/0.41	0.81/0.88	0.72/0.70
	Compression force at 25% [kPa]		785	515	200	315	790	835
	Rework-ability*		● ● ● ●	● ● ● ●	●	● ●	● ● ● ●	● ● ● ●
	Anti-repulsion*		● ● ● ●	● ● ● ●	●	●	● ● ● ●	● ● ● ●

* Assessment is done only in relation to other products of this assortment


● Black

Special foam tapes


For improved reworkability

These products focus on excellent reworkability, which is provided by specific, tailor-made adhesive designs. Additionally, this series, like the other foam assortments, offers excellent impact resistance and bonding performance.


Features



Reworkability




Best bonding




Impact resistance

Typical applications



Component mounting



Battery wrapping






Battery mounting



Back cover mounting

Assortment overview

	tesa® 761xx	tesa® 471x	tesa® 473x
Design			
Color	Black	Translucent white	Translucent white
Adhesive	Synthetic rubber	Specialty	Structured specialty
Backing	PET	PU	-
Removal process	Fast and residue-free removal at elevated temperatures	Splittable design, removable by solvents	Structured surface, residue-free removable by solvents
Special features	Quick bonding, LSE performance	×	Removable by solvents
Thickness	50 µm	○ 4715	○ 4735
	80 µm	○ 4718	○ 4738
	100 µm	○ 4710	
	150 µm		
	200 µm		
	250 µm		
	300 µm		
Product performance	Reference product	● 76108	○ 4718
	Peel adhesion [N/cm; initial/ultimate]	7.0/7.0	7.0
	Push-out [N]	230	230
	DuPont [J; xy/z]	0.7/0.6	0.7/0.8

○ Translucent ○ White ● Black

Bond & Detach®

Stretch-release tapes for residue-free removability

Our Bond & Detach® solutions have revolutionized the removability of adhesives. This tape enables the permanent mounting of components with the option of removing them without residues. Bond & Detach® uses a unique adhesive technology for demanding bonding applications, that provides the option of being removed residue-free by stretching.

The patented technology was developed by tesa and offers the possibility of simple and secure debonding during the entire product life cycle – from production to end of life. It can also be used for temporary fixation during production processes or transportation. In addition, the whole assortment provides good impact resistance and bonding strength, even on LSE substrates.

Features

Fast and residue-free removal

Best bonding


Impact resistance

LSE performance

Typical applications




Battery mounting in mobile devices



Mounting of high-value or critical components







Removable mounting of devices or accessories



Temporary fixation of components

Assortment overview

		tesa® 704xx/703xx/706xx	tesa® 672xx	tesa® 648xx	tesa® 705xx	
Design						
Color		White, transparent, black	Translucent white	White	White	
Adhesive		Synthetic rubber	Synthetic rubber	Synthetic rubber	Synthetic rubber	
Backing		-	PU	Specialty	Specialty	
Special features		Best bonding, light blocking	Very good impact resistance	Excellent impact and tear resistance	Anti-repulsion and shear resistance at elevated temperatures	
Thickness	80 µm		○ 67208			
	100 µm		○ 70410 ● 70610	○ 67210	○ 64810	
	150 µm		○ 70315 ○ 70415 ● 70615	○ 67215	○ 64815 ○ 64816	
	200 µm		○ 70420 ○ 70620		○ 64820	
	250 µm		○ 70425 ● 70625		○ 64825	
	300 µm		○ 70430 ● 70630		○ 64830	
	350 µm		○ 70435 ● 70635			
	400 µm		○ 70440 ● 70640			
	500 µm		○ 70350 ● 70650		○ 70550	
	650 µm		○ 70465 ● 70665			
	800 µm		○ 70480 ● 70680			
	1000 µm		○ 70499 ● 70699			
	1300 µm		● 70697			
Product performance	Reference product		○ 70415 ○ 70315 ● 70615	○ 67215	○ 64815	○ 70525*
	Peel adhesion [N/cm; initial/ulti-mate]	SUS	13.0/13.0	9.0/9.0	11.0/11.0	13.0/13.0
		PE	7.0/7.0	6.0/6.0	8.0/8.0	9.0/9.0
		Black battery pouch	8.0/8.0	7.0/7.0	8.0/8.0	Upon request
	DuPont [J; xy/z]		0.7/0.3	1.0/0.7	1.1/0.8	1.0/0.7
	Tumbler [cycles]		Upon request	400	>500	Upon request
	Removing force [N/cm]		4.0	5.0	4.0	6.0

* Deviating thickness

○ Transparent ○ Translucent ○ White ● Black

Structural bonding solutions

The best reliability for the toughest demands

tesa® structural bonding solutions provide high structural bonding performance to a wide variety of substrates. They withstand the harshest conditions by combining outstanding chemical and aging resistance. The processing of these adhesive systems is simplified due to excellent die cuttability, immediate handling stability after activation, and low oozing.


Heat-activated films

tesa® HAF and tesa® XPU are thermosetting adhesive systems. An irreversible cross-linking reaction is initiated by heat and pressure starting at temperatures above 110°C, resulting in extremely strong bonds.

Low-temperature reactive films

Our low-temperature reactive films tesa® LTR and tesa® LTC have been designed for activation at moderate temperatures. The cross-linking starts at a bond-line temperature above 75°C.

Features



Best bonding



Chemical resistance




Impact resistance




Temperature and humidity resistance


Typical applications




Component mounting



Lens and back cover mounting



Soft goods and accessories



FPC bonding

Assortment overview

		Heat-activated films		Low-temperature reactive films	
		tesa® HAF	tesa® XPU	tesa® LTR	tesa® LTC
Design					
Color		Black, amber	Black, translucent	Black, white, translucent	Black
Adhesive		Nitrile rubber/phenolic resin	Cross-linkable polyurethane	Cross-linkable polyurethane	Cross-linkable polyurethane
Activation temperature [°C]		>120	>110	>75	>75
Special features		Temperature resistance, chemical resistance	Impact resistance, low bonding pressure	Impact resistance, wettability on fabrics	Impact resistance, chemical resistance
Thickness	10 µm	● 58469			
	20 µm	● 58477			
	25 µm		● 58701 ○ 8701		
	30 µm	● 58471 ○ 8471 ● 58470		○ 8711	
	50 µm		● 58702 ○ 8702	● 58460 ○ 8710 ○ 8722	● 58662
	60 µm	○ 8472			
	80 µm	● 58473 ○ 8473			
	100 µm	● 58474 ○ 8474	● 58704 ○ 8704	● 58484 ○ 8714	● 58664
	125 µm	● 58475 ○ 8475			
	150 µm	● 58476 ○ 8476	● 58706 ○ 8706	● 58486	
	200 µm	● 58478 ○ 8478	● 58708 ○ 8708	● 58488	
	300 µm			● 58489	
Product performance	Reference product	● 58474	● 58704	● 58484	● 58664
	Reference substrate	SUS/SUS	AL/PC	PC/PC	AL/AL
	Push-out [MPa]	>5.5	>4.0	>5.5	>4.0
	DuPont [J; xy/z]	>0.5	>3.5	>4.0	>1.0
	Reliability*	● ● ● ●	● ● ●	● ● ●	● ● ● ●
	Chemical resistance*	● ● ● ●	● ●	● ●	● ● ●

* Assessment is done only in relation to other products of this assortment

○ Amber ○ Translucent ○ White ● Black


Double-sided electrically conductive tapes

For applications requiring grounding


By offering a broad assortment of filled acrylic adhesive systems, with a balance between electrical conductivity and adhesive properties, we are able to provide the best solution for your requirements. Simply decide what is the most important for your application: bonding performance, conductivity, or a balance of both.

Our double-sided tapes are available with two different backings. The woven backing offers a higher tear resistance, very good dimensional stability, and better reworkability, while the nonwoven backing provides faster wetting, excellent conformability, and very good die cuttability.


Typical applications



FPC grounding



FPC on SUS



Component grounding

Features

High bonding performance

High conductivity

Anti-repulsion

Assortment overview


	tesa® 6025x/6026x	tesa® 6036x	tesa® 6037x	tesa® 6038x	tesa® EC HAF 5845x	
Design						
Color	Gray	Gray	Black	Gray	Black	
Adhesive	Conductive acrylic	Conductive acrylic	Conductive acrylic	Conductive acrylic	Conductive structural adhesive	
Backing	Woven, nonwoven	Woven	Woven, nonwoven	Woven, nonwoven	-	
Special features	Balanced properties	High bonding strength, high conductivity	Best conductivity	Best bonding strength, repulsion resistance	Heat-activated structural bonding film, temperature and humidity resistance	
Thickness	17 µm	● 60267				
	25 µm	● 60261				
	30 µm			● 60371	● 58451	
	35 µm	● 60260				
	50 µm	● 60262	● 60362	● 60372	● 60381 ● 60382	● 58452
	55 µm	● 60251 ● 60252				
	70 µm	● 60253				
	100 µm	● 60254	● 60364	● 60374	● 60384 ● 60385	
	150 µm	● 60255				
	200 µm	● 60256				
	250 µm	● 60257	x			
Product performance	Reference product	● 60252 ● 60262	● 60362	● 60372	● 60381 ● 60382	● 58452
	Peel adhesion [N/cm; initial/ultimate] SUS	5.4/8.3	7.0/8.0	4.3/5.6	8.0/10.0	n.a.
	Dynamic shear [N]	n.a.	n.a.	n.a.	n.a.	>7
	Contact resistance [mΩ.inch²]	0.05	0.01	0.01	0.06	0.05
	Surface resistance [mΩ.sq]	0.2	0.1	0.1	0.3	0.5
	Shielding effectiveness [-dB]	>50	>60	>50	>50	~40
						● Black ● Gray


Single-sided electrically conductive tapes

For shielding and covering applications

Covering and shielding applications are broad and have different requirements for conductivity, adhesion, and design. Our single-sided ECT assortment meets the latest requirements for shielding and appearance.

Features


EMI shielding

Modern appearance


Typical applications



MLB covering







MLB shielding



Wire wrapping

Assortment overview

	tesa® 6023x	tesa® 6053x	tesa® 6031x	tesa® 6034x
Design				
Color	Matte black	Orange	Orange	Gray
Adhesive	Conductive acrylic	Conductive acrylic	Conductive acrylic	Conductive acrylic
Backing	Fabric, copper	Copper	Copper	Fabric
Special features	Modern, matte black design	Excellent bonding	Low-pressure activation, high conductivity	Low-pressure activation, high conductivity
Thickness	25 µm	● 60231		
	30 µm		● 60537	● 60347
	35 µm	● 60232		
	45 µm	● 60238		
	50 µm		● 60318	● 60348
	55 µm	● 60234		
Product performance	Reference product	● 60232	● 60537	● 60317
	Peel adhesion [N/cm; initial/ultimate]	SUS 3.5/4.5	6.3/7.5	4.6/5.3
	Contact resistance [mΩ.inch²]	0.05	0.05	0.03
	Surface resistance [mΩ.sq]	0.2	0.2	0.2
	Shielding effectiveness [-dB]	>50	>70	>70

● Matte black ● Gray ● Orange

Didn't find what you were looking for?

We have more options available in our portfolio, and by partnering with you we can create unique and specialized products that meet your individual demands. Simply write to us or contact your local representative: electronics@tesa.com





Single-sided electrically conductive foam tapes


For conductive gap filling

Our single-sided electrically conductive foam tapes can be used for shielding, grounding, and filling gaps. They will provide either outstanding conformability and recovery properties or very high abrasion resistance, depending on the foam material chosen. All series in this assortment have very good shock-absorbing and cushioning properties.

Features


EMI shielding



Electrical conductivity


Compressibility

Typical applications




FPC grounding



MLB grounding

Assortment overview

		tesa® 6021x	tesa® 6068x	tesa® 6024x
Design				
Color		Gray	Gray	Gray
Adhesive		Conductive acrylic	Conductive acrylic	Conductive acrylic
Backing		Soft foam	Ultrasoft foam	Gasket foam
Special features		Excellent electrical conductivity	Excellent compressibility	Abrasion resistance
Thickness	200 µm	● 60213		
	300 µm	● 60214		● 60246
	500 µm		● 60685	● 60248
	700 µm		● 60687	● 60249
	1,000 µm		● 60688	
	1,500 µm	● 60217		
	2,000 µm	● 60218		
Reference product		● 60214	● 60685	● 60248
Product performance	Peel adhesion [N/cm; initial/ultimate]	SUS 4.8/8.3	6.0/8.0	4.8/6.3
	Contact resistance [mΩ.inch²]	0.03	0.03	0.03
	Surface resistance [mΩ.sq]	0.2	0.2	0.2
	Shielding effectiveness [-dB]	>70	>60	>70
	Compression force at 50% [N/cm²]	<50	<6	<55
	Recovery rate after 24h [%]	90	96	96


● Gray

Thermal management tapes


Keeping electronic devices cool

tesa® TMT 6074X provides superior thermal transfer performance with excellent bonding properties. It delivers very good surface wet-out on substrates due to the transfer tape design which helps to maximize the thermal transfer efficiency in electronic devices. The available thickness range starting from ultrathin 10 µm ending at 100 µm offers more flexibility in the device design.


Features




Excellent thermal conductivity




Strong bonding strength



Excellent surface wet-out




High breakdown voltage




Ultrathin design


Typical applications



Vapor chamber mounting




5G-antenna mounting




Heat pipe mounting

Assortment overview

tesa® 6074x		
Design		
Color	White	
Backing	-	
Thickness	10 µm	○ 60742
	30 µm	○ 60743
	50 µm	○ 60744
	100 µm	○ 60745
Reference product	○ 60744	
Product performance	Peel adhesion [N/cm; initial/ultimate]	SUS 5.0
	Thermal conductivity [W/m x K]	1.0
	Wetting [%]	84
	Break-down voltage [kV]	2.9

○ White

Cooling scenario



Covering tapes

More functionality for electronic devices

Electronic components are evolving one generation after the other, just like our solutions for covering tape. Our portfolio consists of polyester and polyimide tapes.

Features


Anti-repulsion

Light blocking


High bonding

Modern appearance


Typical applications



Light blocking in LCD backlight unit



Protection of magnetic sheet and coil in wireless charging



Insulation on PCB and FPC

Assortment overview

	tesa® 79xx	tesa® 71xx	tesa® 673xx	tesa® 663xx	
Design					
Color	Matte black	Natural black	Matte black	Amber	
Adhesive	Black tackified acrylic	Black tackified acrylic	Tackified acrylic	Tackified acrylic	
Backing	PET	PET	PI	PI	
Special features	Light blocking, anti-repulsion, dielectric insulation	Light blocking, anti-repulsion, high bonding	Light blocking, anti-repulsion, dielectric insulation, heat resistance	Anti-repulsion, dielectric insulation, heat resistance	
Thickness	5 µm	● 7905			
	8 µm	● 7908			
	10 µm	● 7910		● 67310	
	20 µm	● 7920		● 67320	● 66320
	30 µm	● 7930		● 67330	● 66330
	50 µm	● 7950	● 7250	● 67350	● 66350
	60 µm		● 7160		
	80 µm		● 7180		
	100 µm		● 7100		
Product performance	Reference product	● 7950	● 7250	● 67350	● 66350
	Peel adhesion [N/cm; initial/ultimate] SUS	4.0	4.2	3.5	4.0
	Light blocking [optical density]	5.7	>6	2.6	n.a.
	Insulation [kV, dielectric breakdown voltage]	5.5	5.0	3.6	3.6
	Anti-repulsion*	● ● ● ●	Upon request	● ● ● ●	● ● ● ●

* Assessment is done only in relation to other products of this assortment


● Amber ● Matte/Natural black

Display tapes


Optically clear design with special features

Our comprehensive assortment is designed to provide a solution for every display application. All our materials are produced in a clean room and fulfill optically clear requirements, while also being environmentally stable and compatible with other display layers.

Typical applications



Cover lens lamination




Touch panel lamination

New OCA developments


In addition to our active assortment, we are developing new materials to support handheld devices with **foldable and curved-edge displays**, as well as backside **cushioning tape**. Furthermore, we are developing new **OCA tapes for the automotive industry**.

Contact us to find out what's in our product development pipeline: electronics@tesa.com



Flexible layers


Laminating flexible layers within a foldable or rollable display requires excellent peel adhesion and very good bending properties. For some special substrates like silver nanowire, an OCA tape with good compatibility is required. The first of such products will be available in May.



Curved display

Laminating a curved cover lens to a flexible OLED display requires low tack for easy lamination and good gap filling to cover ink steps. After UV curing, tapes need to show high bonding strength, resistance to repulsion forces, and very good reliability.

NEW




Assortment overview

	tesa® 698xx	tesa® 696xx	tesa® 694xx	tesa® 6156x	tesa® 6153x		
Design							
Color	Transparent	Transparent	Transparent	Transparent	Beige		
Type	UV-curable	UV-curable	PSA	PSA	PSA		
Special features	Outgassing resistant	Excellent gap filling	Lamination of films	Low dK, low WVTR	Moisture blocking		
Thickness*	25 µm		○ 69401	○ 61562	● 61531		
	50 µm	○ 69802	○ 69402	○ 61563	● 61533		
	75 µm			○ 61564			
	100 µm	○ 69804	○ 69604	○ 69404			
	125 µm		○ 69605	○ 69405			
	150 µm	○ 69806	○ 69606				
	175 µm		○ 69607				
	200 µm	○ 69808	○ 69608				
	300 µm	○ 69812	○ 69612				
Product performance	Reference product	○ 69804	○ 69604	○ 69404	○ 61563* ● 61533*		
	Peel adhesion [N/cm; ultimate]	Glass	10.2	11.1	6.9	5.0	6.5
		PET	7.6	7.9	4.8	3.3	6.0
		PC	9.8	10.0	7.0	4.7	6.8
	Trans-mission [%]	>99	>99	>99	>99	n.a.	
	Haze [%]	<0.5	<0.5	<0.5	<0.5	n.a.	
	Refractive index	1.48	1.48	1.48	1.52	1.52	
	Gap filling [%]	30	25	10	<10	<10	
	Dielectric constant ¹	4.7	4.5	4.9	2.56	2.92	
	G' [kPa] ²	250	130	107	550	Upon request	
	WVTR ³ [g/m ² ·day]	n.a.	n.a.	n.a.	0.9	0.4 ⁵	
	Lag time ⁴ [h]	n.a.	n.a.	n.a.	25	10,000	

* Further thicknesses might be available upon request. ○ Transparent ● Beige

¹100 kHz
² 25°C, 1 Hz
³ 38°C, 90% rel. humidity, 1 mm
⁴ 60°C, 90% rel. humidity, 6.5 mm gap
⁵ WVTR after all getter is used up

Global presence



tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Our company sees its orientation towards international quality, environmental, and occupational safety standards as a matter of course.

Please find more information regarding our international certifications under: www.tesa.com/certifications