

tesa® Professional 60100 Fibre Glass



Product Information

Fibreglass Tape

Product Description

tesa® 60100 self-adhesive fibreglass tape features the latest developments in joint tape technology.

With its very strong and flat fibreglass mesh, tesa® 60100 offers durable and long lasting drywall/plaster board joints.

The excellent adhesion and the very good tensile strength allow one-time application and smooth finished joints.

Application Fields

tesa® 60100 is also used for fixing and patching small holes and cracks

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	fibreglass	•	Total thickness	260 μm
•	Type of adhesive	acrylic			10.2 mils
			•	Color	white

Properties/Performance Values

•	Elongation at break	2 %	•	Tensile strength	102 N/cm
					58.2 lbs/in

Adhesion to Values

• Steel	0.7 N/cm
	6.4 oz/in



tesa® Professional 60100 Fibre Glass

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

