

# 51721

## Product Information



Dotted bridging label for belt-driven splicers

### Product Description

tesa® EasyBridge 51721 is a die-cut paper label for belt area coverage on belt driven reel stands in the printing industry. It is preferably used in combination with tesa EasySplice® 51780 PV16 PrintLine Plus.

tesa® 51721 features especially

- Noses of 3 mm length to ensure exact positioning
- Circular holes for perfect contact of the splice in the belt area
- Crosswise perforation to allow tear off pieces of suitable length for most common belt widths

Color: White

### Product Features

- Noses of 3 mm length to ensure exact positioning
- Circular holes for perfect contact of the splice in the belt area
- Crosswise perforation to allow tear off pieces of suitable length for most common belt widths

### Application Fields

tesa® 51721 is particularly suitable for:

- Belt area covering for flying splice applications in the printing industry

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                   |                   |         |       |
|-------------------|-------------------|---------|-------|
| • Backing         | flat paper        | • Color | white |
| • Total thickness | 92 µm<br>3.6 mils |         |       |

### Properties/Performance Values

- |                |                     |
|----------------|---------------------|
| • Paper weight | 79 g/m <sup>2</sup> |
|----------------|---------------------|



# 51721

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51721>