



tesa® 53131

Product Information



Bandoliering tape for different components

Product Description

tesa® 53131 is a medium grade paper tape designed for bandoliering / sequencing of axial leaded components such as capacitors, resistors, and diodes.

Product Features

- Temperature resistance
- Thin backing for good
- Conformability
- Natural rubber adhesive for good belting performance

Application Fields

- Sequencing axial leaded components
- Bandoliering axial leaded components

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|-------------------|----------|
| • Backing | slightly-creped paper | • Total thickness | 170 µm |
| • Type of adhesive | natural rubber | | 6.7 mils |

Properties/Performance Values

- | | | | |
|-----------------------|------|--------------------|-------------|
| • Elongation at break | 13 % | • Tensile strength | 53 N/cm |
| | | | 30.3 lbs/in |

Adhesion to Values

- | | |
|---------|------------|
| • Steel | 4 N/cm |
| | 36.5 oz/in |



tesa[®] 53131

Product Information

Additional Information

Colors: chamois, blue

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=53131>