



# **Product Information**

# Standard Grade Tear Tape

### **Product Description**

tesa 53488 is a tensilized polypropylene tear tape featuring a 60 micron backing and an aggressive synthetic adhesive. This product exhibits excellent bonding on both solid and corrugated cardboard surfaces. Because of its unique backing and excellent tack, tesa 53488 will not exhibit shrinkage or "lift off" after application to corrugated cardboard. This product is ideal for most pull tab and tear strip applications.

# **Application Fields**

- Industrial and consumer cartons
- Padded shipping envelopes, express delivery and courier envelopes
- Corrugated cartons and boxes

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

<ul><li>Backing</li><li>Type of adhesive</li></ul>	TPP synthetic rubber	Total thickness	85.5 μm 3.4 mils	
Properties/Performance Values				
Elongation at break	32 %	Tensile strength	215 N/cm 122.8 lbs/in	

#### **Adhesion to Values**

•	Steel	6 N/cm
		54.8 oz/in





**Product Information** 

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 02/29/24 – en-TT