

tesa® 53490

Product Information

Performance Grade Tear Tape

Product Description

tesa® 53490 is a tensilized polypropylene teartape with an aggressive adhesive that exhibits excellent bonding on both solid and corrugated cardboard surfaces. Because of the unique backing and its excellent tack, 53490 will not exhibit shrinkage or "lift off" after application to corrugated cardboard. 53490 also exhibits excellent nick resistance and its high tensile strength makes it ideal for pull tab and tearstrip applications.

Application Fields

- Tear strip for industrial and consumer cartons
- For use on padded shipping envelopes, express delivery and courier envelopes
- Use on corrugated cartons and boxes

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	TPP	•	Total thickness	108 µm
•	Type of adhesive	synthetic rubber			4.3 mils

Properties/Performance Values

•	Elongation at break	30 %	•	Tensile strength	230 N/cm
					131.3 lbs/in

Adhesion to Values

• Steel 7.5 N/cm 68.5 oz/in



tesa® 53490

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

